

# Data Sheet

## FUJITSU Server PRIMERGY TX1320 M4 Tower Server

Ultra-compact advanced server to grow your business

FUJITSU Server PRIMERGY will give you the servers you need to power any workload and changing business requirements. As business processes expand so does the need for applications. Each has its own resource footprint, so you need a way to optimize your computing to better serve your users. PRIMERGY systems will help you match your computing capabilities to your business priorities with our complete portfolio of expandable PRIMERGY tower servers for remote and branch offices, versatile rack-mount servers as well as hyper-converged multi-node servers. They convince by business proven quality with a wide range of innovations, highest efficiency cutting operational cost and complexity, provide more agility in daily operations, and integrate seamlessly to let help you concentrate on core business functions.

Perfect for small and medium businesses as well as branch offices, FUJITSU Server PRIMERGY TX tower systems are robust and cost-efficient servers by providing rock solid reliability. Additionally they are characterized by simple IT operations, low power consumption and quiet operation so that they can be handled by non-technically trained staff and can be used in standard office environments. By the way: Almost all PRIMERGY TX servers can be rack-mounted to offer best flexibility.

### PRIMERGY TX1320 M4

The unique ultra-compact FUJITSU Server PRIMERGY TX1320 M4 has advanced technology ideal for most industry verticals, small and medium-sized enterprises (SME), space-constrained environments, retail premises or branch offices. The performance-oriented yet cost-effective mono-socket design supports the latest Intel® Xeon® E-2100 product family processors, affordable Intel® Core™ i3, Pentium®, Celeron® processor options plus up to 64GB RAM at 2,666 MT/s to boost performance for appropriately

sized standard business workloads, including virtualized ones (such as: File/Print, Email, ERP/CRM, Messaging, Centralized data storage) and industry specific applications. Institutions with special legal requirements such as medical, governmental, legal, or financial offices can benefit from the server's secure and robust storage and transmission features, which include up to eight high quality 2.5-inch storage devices (including up to four ultra-fast NVMe devices for demanding applications), powerful RAID controllers, versatile and affordable backup and networking options together with TPM 2.0 capability. High efficiency (94%), redundant power supplies and the innovative Fujitsu Battery Backup Unit enhance reliability and protect customer investment. This ultra-compact, silent server with the Advanced Thermal Design Technology is designed for deployment flexibility – it can be deployed in offices, on rack shelves, industrial areas and even on desks at temperatures from 5°C to 45°C. New generation technologies include M.2 modules for efficient OS installation along with Dual microSD capability for VMware ESXi, plus the latest USB 3.1 Gen 2 ports. Furthermore, the TX1320 M4 server features the iRMC S5 and the Fujitsu ServerView suite, designed for easy and effective management across the entire server lifecycle, including deployment, installation and administration.



# Features & Benefits

Main Features	Benefits
<p><b>Ultra-compact server with advanced technology</b></p> <ul style="list-style-type: none"> <li>Wide choice of the Intel® Xeon® E-2100 product family processors and affordable Core™ i3, Pentium® and Celeron® options. Up to 64 GB DDR4 ECC memory (4 DIMMs at 2,666 MT/s) is supported for high-speed, reliable performance. Note: Celeron® available only via special release request.</li> </ul>	<ul style="list-style-type: none"> <li>Power packed performance across Small and Medium Enterprises, and most Industry verticals. The latest compute and memory technology offer high flexibility to handle appropriately sized, individual or virtualized standard business workloads (file/ print, web, email, messaging, ERP/CRM), or more demanding industry specific applications.</li> <li>The server can handle both demanding low-latency storage applications or offer cost-effective storage with backup capability. With up to 8 devices, the server can handle most small office dataset or data consolidation requirements. Dual LAN support offers reliable data connectivity for standard requirements right out of the box, while advanced options support higher data-rate business specific needs e.g. virtualized environments or centralized data sharing over the network.</li> <li>The server grows with your business. Add advanced Fujitsu RAID controllers for reliable data handling (high grade SAS 3.0 with up to 4/8 GB cache) or networking options (including 10/25Gb Ethernet controllers) for high-speed data transmission.</li> <li>Adds security capabilities to protect valuable enterprise data from unauthorized access - ideal for institutions with legal requirements for high-security data storage.</li> <li>M.2 devices are designed for flexible boot requirements – option of cost-effective and reliable mirrored SATA modules or deploy high-speed NVMe, while Dual microSD modules offer mirrored support for VMware ESXi. New high data rate USB is suited for the latest generation peripheral devices.</li> <li>Good for the environment, and your business economics – the high efficiency, redundant power supplies offer enhanced reliability and lower energy expenditure. A cost optimized alternative to power supply redundancy, the Battery Backup Unit protects your valuable investment by supporting safe power down and expanded time of operation in case of power loss.</li> <li>Fits almost everywhere and saves space - ideal for small offices, at point of sales or even in compact racks or placed on shelves. Low noise emissions and expanded range of operation (5 °C to 45 °C) with Fujitsu's Cool-safe® Advanced Thermal Design technology make the server ideal for offices, showrooms, desks all the way to industrial environments – all without the need for expensive cooling.</li> <li>Reduce your IT administrator's burden by simplifying server management via a comprehensive software suite which can include the iRMC S5 and the Fujitsu ServerView suite, which includes tools for installation and deployment, permanent status monitoring and control. Enhanced serviceability with easy, fast and comfortable access to critical components.</li> </ul>
<p><b>Versatile Storage and networking capability</b></p> <ul style="list-style-type: none"> <li>8 x hot-plug 2.5-inch (SAS/SATA) devices (including up to 4x NVMe) plus RDX backup. Powerful SAS 3.0 RAID Controllers with up to 8 GB cache are available. Redundant (2x1GbE) LAN as standard, plus 25/10 Gb Ethernet controller options.</li> </ul>	
<p><b>Investment protection</b></p> <ul style="list-style-type: none"> <li>Future ready with 4x PCIe Gen3 slots.</li> </ul>	
<p><b>Security optimized design</b></p> <ul style="list-style-type: none"> <li>TPM 2.0 support plus Fujitsu's secure 3-way lock for server access.</li> </ul>	
<p><b>Latest generation technologies for improved performance</b></p> <ul style="list-style-type: none"> <li>Supports 2x M.2 modules: 1x SATA; 1x NVMe/SATA, plus Dual microSD modules, also offers new 3.1 Gen2 USB ports (Total of 2x 3.1 Gen2 plus 2x 3.1 Gen1, 4x 2.0, Internal 2x 3.1 Gen1 ports).</li> </ul>	
<p><b>Improved economics with energy efficiency and reliability</b></p> <ul style="list-style-type: none"> <li>High efficiency 450W power supplies (94% efficiency) are available with both hot-plug capability and redundancy. Fujitsu Battery Backup Unit, an optional Internal UPS in modular PSU formfactor, 5 years lifetime, fully integrated.</li> </ul>	
<p><b>Excellent flexibility – deploy anywhere</b></p> <ul style="list-style-type: none"> <li>Ultra-small form factor with silent operation.</li> </ul>	
<p><b>Full server management features and easy accessibility</b></p> <ul style="list-style-type: none"> <li>Comprehensive software management suite available with the iRMC S5 and the Fujitsu ServerView Suite. Screw-less chassis with hot-plug 2.5-inch devices, hot-plug power supplies and "Easy Rails" for 3.5-inch storage disks.</li> </ul>	

# Technical details

<b>PRIMERGY TX1320 M4</b>			
Base unit	PRIMERGY TX1320 M4 SFF/Std. PSU	PRIMERGY TX1320 M4 SFF/Red. PSU	PRIMERGY TX1320 M4 LFF/Std. PSU
Housing types	Ultra-compact form-factor	Ultra-compact form-factor	Ultra-compact form-factor
Storage drive architecture	2.5-inch	2.5-inch	3.5-inch
Power supply	Standard	Hot-plug	Standard
Product Type	Mono Socket Tower Server	Mono Socket Tower Server	Mono Socket Tower Server
<b>Mainboard</b>			
Mainboard type	D3673		
Chipset	Intel® C246		
Processor quantity and type	1 x Intel® Xeon® E-2100 processor family / Intel® Core™ i3 processor / Intel® Pentium® processor		
<b>Processor</b>			
	Intel® Xeon® processor E-2186G (6C/12T, 3.80 GHz, up to 4.3 GHz, 2,666 MHz)		
	Intel® Xeon® processor E-2176G (6C/12T, 3.70 GHz, up to 4.3 GHz, 2,666 MHz)		
	Intel® Xeon® processor E-2174G (4C/8T, 3.80 GHz, up to 4.3 GHz, 2,666 MHz)		
	Intel® Xeon® processor E-2146G (6C/12T, 3.50 GHz, up to 4.2 GHz, 2,666 MHz)		
	Intel® Xeon® processor E-2144G (4C/8T, 3.60 GHz, up to 4.2 GHz, 2,666 MHz)		
	Intel® Xeon® processor E-2136 (6C/12T, 3.30 GHz, up to 4.2 GHz, 2,666 MHz)		
	Intel® Xeon® processor E-2134 (4C/8T, 3.50 GHz, up to 4.2 GHz, 2,666 MHz)		
	Intel® Xeon® processor E-2126G (6C/6T, 3.30 GHz, up to 4.1 GHz, 2,666 MHz)		
	Intel® Xeon® processor E-2124G (4C/4T, 3.40 GHz, up to 4.1 GHz, 2,666 MHz)		
	Intel® Xeon® processor E-2124 (4C/4T, 3.30 GHz, up to 3.9 GHz, 2,666 MHz)		
	Intel® Pentium® processor G5400 (2C/4T, 3.70 GHz, 2,666 MHz)		
	Intel® Core™ i3-8100 processor (4C/4T, 3.60 GHz, 2,400 MHz)		
	Intel® Celeron® processor G4900 (2C/2T, 3.10 GHz, 2,400 MHz)		
Memory slots	4		
Memory slot type	DIMM (DDR4)		
Memory capacity (min. - max.)	4 GB - 64 GB		
Memory protection	ECC		
Memory notes	Mix and match possible; with dual channel operation better performance (2 modules with equal capacity necessary). Single channel (1 module) configuration possible.		
<b>Memory options</b>			
	4 GB (1 module(s) 4 GB) DDR4, unbuffered, ECC, 2,666 MHz, PC4-2666, DIMM, 1Rx8		
	8 GB (1 module(s) 8 GB) DDR4, unbuffered, ECC, 2,666 MHz, PC4-2666, DIMM, 1Rx8		
	16 GB (1 module(s) 16 GB) DDR4, unbuffered, ECC, 2,666 MHz, PC4-2666, DIMM, 2Rx8		
Memory modules notes	2,666 MHz memory modules		
<b>Interfaces</b>			
USB 2.0 ports	4 (4x external rear)		
USB 3.0 ports	4 (2x internal, 2x external front, USB 3.0 is now known as USB 3.1 Gen 1). <b>Server also has 2x external rear USB 3.1 Gen 2 ports</b>		
Graphics (15-pin)	1 analog graphics interface derived from iRMC (up to 1600x1200 or 1920x1080 at 16bpp)		
Serial 1 (9-pin)	1 serial RS-232-C		
LAN / Ethernet	2 x1 Gb/s Ethernet; RJ45		
Management LAN (RJ45)	1 x dedicated management LAN port for iRMC S5 (10/100/1000 Mbit/s) Management LAN traffic can be switched to shared onboard Gbit LAN port		
<b>Onboard or integrated Controller</b>			
RAID controller	Optionally integrated RAID 0/1 or RAID 5/6 controller for SAS base units (occupies one PCIe slot). All hardware storage controller options are described under Components		
SATA Controller	Intel® C246, 2 ports used for accessible drives		
SATA controller type notes	4 port for internal SATA HDDs with RAID 0, 1, 10 for Windows and Linux		

<b>Onboard or integrated Controller</b>			
<b>LAN Controller</b>	Intel® i210 onboard 2 x 10/100/1000 Mbit/s Ethernet iSCSI, PXE-Boot and WoL are supported		
<b>Remote management controller</b>	Integrated Remote Management Controller (iRMC S5) IPMI 2.0 compatible		
<b>Trusted Platform Module (TPM)</b>	TPM 2.0 module (option)		
<b>Slots</b>			
<b>PCI-Express 3.0 x4</b>	1 x Low profile notched		
<b>PCI-Express 3.0 x8</b>	2 x Low profile notched		
<b>PCI-Express x1</b>	1 x Low profile PCI-Express 3.0		
<b>Slot Notes</b>	In SAS configuration 1x PCI-Express occupied by modular RAID controller.		
<b>PCI-Express 3.0 x4</b>	1 x notched	1 x notched	1 x notched
<b>PCI-Express 3.0 x8</b>	2 x notched	2 x notched	2 x notched
<b>Drive bays</b>			
<b>Storage drive bays</b>	3.5-inch non hot-plug or 2.5-inch hot-plug SAS/SATA or 2.5-inch NVMe drives		
<b>Storage drive bay configuration</b>	Not upgradeable in the field.		
<b>Accessible drive bays</b>	1 x 3.5/1.6-inch for backup devices 1 x 5.25/0.5-inch for CD-RW/DVD		
<b>Drive bays</b>			
<b>Storage drive bays</b>	Max. 8x (4x + 4x) x 2.5-inch hot-plug	Max. 2 x 3.5-inch non hot-plug SATA	
<b>Accessible drive bays</b>	1 x 3.5/1.6-inch for backup devices 1 x 5.25/0.4-inch for CD-RW/DVD	1 x 3.5/1.6-inch for backup devices 1 x 5.25/0.4-inch for CD-RW/DVD	
<b>Fan Configuration</b>			
<b>Number of fans</b>	3		
<b>Fan notes</b>	Processor fan, rear fan, drive fan, additional drive fan if 8x HDD extension is used		
<b>Number of fans</b>	1		
<b>Fan configuration</b>	1 standard fan		
<b>Fan notes</b>	non redundant / non hot-plug		
<b>Operating panel</b>			
<b>Operating buttons</b>	On/off switch NMI button Reset button		
<b>Status LEDs</b>	System status (orange / yellow) Identification (blue) Hard disks access (green) Power (orange / green) At system rear side: System status (orange / yellow) Identification (blue) LAN connection (green) LAN speed (green / yellow) CSS (yellow)		

**Operating Systems and Virtualization Software**

<b>Certified or supported operating systems and virtualization software</b>	Windows Server 2019 Datacenter
	Windows Server 2019 Standard
	Windows Server 2019 Essentials
	Windows Server Datacenter, version 1809
	Windows Server Standard, version 1809
	Hyper-V Server 2016
	Windows Server 2016 Datacenter
	Windows Server 2016 Standard
	Windows Server 2016 Essentials
	Windows Storage Server 2016 Standard
	Windows Server Datacenter, version 1709
	VMware vSphere™ 6.5
	VMware vSphere™ 6.7
	SUSE® Linux Enterprise Server 12
Red Hat® Enterprise Linux 7	

**Operating system notes**

<b>Operating system release link</b>	<a href="http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfbf3230473">http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfbf3230473</a>
--------------------------------------	---

**Server Management**

<b>Standard</b>	<ul style="list-style-type: none"> <li>ServerView Suite (Deploy) <ul style="list-style-type: none"> <li>ServerView Installation Manager</li> <li>ServerView Scripting Toolkit</li> </ul> </li> <li>ServerView Suite - Control <ul style="list-style-type: none"> <li>ServerView Operations Manager incl. PDA and ASR &amp; R</li> <li>ServerView Agents and CIM Providers</li> <li>ServerView Agentless Management</li> <li>ServerView System Monitor</li> <li>SVOM - Event Manager</li> <li>ServerView RAID Manager</li> <li>SVOM - Threshold Manager</li> <li>Power Monitor (monitoring the Power Consumption)</li> <li>Power Management (iRMC)</li> <li>Storage Management (server) with SVOM/SV-RAID</li> </ul> </li> <li>ServerView Suite (Maintain) <ul style="list-style-type: none"> <li>iRMC S5 (Remote Management)</li> <li>System Update Manager (BIOS, Firmware, Windows Drives and SV Agents)</li> <li>Performance management (SVOM)</li> <li>Asset Management</li> <li>Primecollect</li> <li>Customer Self Service</li> <li>Online Diagnostics</li> </ul> </li> <li>ServerView Suite (Integrate) <ul style="list-style-type: none"> <li>ServerView Integration packs for MS System Center, VMware vCenter, VMware vRealize, Nagios and HP SIM</li> </ul> </li> </ul>
<b>Option</b>	<ul style="list-style-type: none"> <li>ServerView Suite (Maintain) <ul style="list-style-type: none"> <li>ServerView eLCM</li> <li>iRMC Advanced Pack incl. Advanced Video Redirection (AVR), video capturing and Virtual Media</li> </ul> </li> </ul>

**Dimensions / Weight**

<b>Floor-stand (W x D x H)</b>	98 x 399 x 340 mm
<b>Dimension notes</b>	without feet
<b>Weight</b>	up to 10 kg

**Environment**

<b>Operating ambient temperature</b>	5 - 45 °C (41 - 113 °F)
<b>Operating temperature note</b>	Cool-safe® Advanced Thermal Design (above 35 °C or below 10 °C) depending on configuration. For detailed information see relevant system configurator.
<b>Operating relative humidity</b>	10 - 85 % (non condensing)
<b>Operating environment</b>	FTS 04230 - Guideline for Data Center (installation specification)

<b>Environment</b>	
<b>Operating environment link</b>	<a href="http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe">http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe</a>
<b>Sound pressure (LpAm)</b>	SATA: 18 dB(A) idle mode / 18 dB(A) operating mode; SAS: 31 dB(A) idle mode / 34 dB(A) operating mode
<b>Sound power (LWAd; 1B = 10dB)</b>	SATA: 3.1 B idle mode / 3.1 B operating mode; SAS: 4.6 B idle mode/ 4.8 B operating mode
<b>Noise notes</b>	Noise emissions depend on operation modes, system configuration and ambient temperature.
<b>Electrical values</b>	
<b>Power supply configuration</b>	1 x standard, 1 x hot-plug, 2 x hot-plug redundant, 1 x hot-plug + 1 x Fujitsu FJBU internal battery backup unit (depending on Model)
<b>Active power (max. configuration)</b>	231 W
<b>Apparent power (max. configuration)</b>	235 VA
<b>Heat emission (max. configuration)</b>	831.6 kJ/h (788.2 BTU/h)
<b>Rated current max.</b>	5 A (100 V) / 2.5 A (240 V)
<b>Active power note</b>	To estimate the power consumption of different configurations use the Power Calculator of the System Architect: <a href="http://configurator.ts.fujitsu.com/public/">http://configurator.ts.fujitsu.com/public/</a>
<b>Power supply</b>	250W standard, 90% (Gold efficiency), 100-240V, 50 / 60Hz 450W hot-plug, 94% (Platinum efficiency), 100-240V, 50 / 60Hz
<b>Compliance</b>	
<b>Global</b>	CB RoHS (Substance limitations in accordance with global RoHS regulations) WEEE (Waste electrical and electronic equipment)
<b>Germany</b>	GS
<b>Europe</b>	CE
<b>USA/Canada</b>	CSA us ULc/us FCC Class A
<b>Japan</b>	VCCI Class A
<b>Russia</b>	GOST-R
<b>South Korea</b>	KC
<b>China</b>	CCC
<b>Australia/New Zealand</b>	C-Tick
<b>Taiwan</b>	BSMI
<b>Compliance link</b>	<a href="https://sp.ts.fujitsu.com/sites/certificates">https://sp.ts.fujitsu.com/sites/certificates</a>
<b>Compliance notes</b>	* Warning: This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.

## Components

<b>Backup Drives</b>	RDX Drive, 320 GB, 500 GB, 1 TB , 25 MB/s, half height, USB 3.0
<b>Optical drives</b>	Blu-ray Disc™ Triple Writer, (6x BD-RW, 8x DVD, 24x CD), ultraslim, SATA I DVD Super Multi ultra slim , (8x DVD; 24x CD), ultraslim, SATA I

<b>Hard disk drives</b>	HDD SATA, 6 Gb/s, 500 GB, 7,200 rpm, 512e, non hot plug, 3.5-inch, economic
	HDD SATA, 6 Gb/s, 6 TB, 7,200 rpm, 512e, non hot plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 4 TB, 7,200 rpm, 512n, non hot plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 2 TB, 7,200 rpm, 512n, non hot plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 2 TB, 7,200 rpm, 512n, hot-plug, 2.5-inch, business critical
	HDD SATA, 6 Gb/s, 2 TB, 7,200 rpm, 512e, hot-plug, 2.5-inch, business critical
	HDD SATA, 6 Gb/s, 1 TB, 7,200 rpm, 512n, non hot plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 1 TB, 7,200 rpm, 512n, hot-plug, 2.5-inch, business critical
	HDD SATA, 6 Gb/s, 1 TB, 7,200 rpm, 512e, non hot plug, 3.5-inch, economic
<b>Hard disk drives</b>	HDD SAS, 12 Gb/s, 900 GB, 15,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
	HDD SAS, 12 Gb/s, 600 GB, 15,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
	HDD SAS, 12 Gb/s, 600 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
	HDD SAS, 12 Gb/s, 600 GB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise
	HDD SAS, 12 Gb/s, 600 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise, SED
	HDD SAS, 12 Gb/s, 300 GB, 15,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
	HDD SAS, 12 Gb/s, 300 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise, SED
	HDD SAS, 12 Gb/s, 300 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
	HDD SAS, 12 Gb/s, 2.4 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise, SED
	HDD SAS, 12 Gb/s, 2.4 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise
	HDD SAS, 12 Gb/s, 1.8 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise, SED
	HDD SAS, 12 Gb/s, 1.8 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise
	HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, hot-plug, 2.5-inch, enterprise
	HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise
	HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise, SED
<b>Solid-State-Drive</b>	SSD SATA, 6 Gb/s, 960 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 0.9 DWPD (Drive Writes Per Day for 5 years)
	SSD SATA, 6 Gb/s, 960 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD (drive writes per day for 5 years)
	SSD SATA, 6 Gb/s, 512 GB, hot-plug, 2.5-inch
	SSD SATA, 6 Gb/s, 480 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 0.9 DWPD (Drive Writes Per Day for 5 years)
	SSD SATA, 6 Gb/s, 480 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3.6 DWPD (Drive Writes Per Day for 5 years)
	SSD SATA, 6 Gb/s, 240 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.4 DWPD (Drive Writes Per Day for 5 years)
	SSD SATA, 6 Gb/s, 240 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3.6 DWPD (Drive Writes Per Day for 5 years)
	SSD SATA, 6 Gb/s, 7.68 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 0.5 DWPD (Drive Writes Per Day for 5 years)
	SSD SATA, 6 Gb/s, 3.84 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.0 DWPD (Drive Writes Per Day for 5 years)
	SSD SATA, 6 Gb/s, 3.84 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD (drive writes per day for 5 years)
	SSD SATA, 6 Gb/s, 1.92 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 0.9 DWPD (Drive Writes Per Day for 5 years)
	SSD SATA, 6 Gb/s, 1.92 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD (drive writes per day for 5 years)
	SSD M.2 SATA, 6 Gb/s, 480 GB, non hot plug, enterprise, 1.4 DWPD (Drive Writes Per Day for 5 years)
	SSD M.2 SATA, 6 Gb/s, 240 GB, non hot plug, enterprise, 1.4 DWPD (Drive Writes Per Day for 5 years)
SSD M.2 SATA, 6 Gb/s, 240 GB, non hot plug, enterprise	
<b>PCIe SSD &amp; SATA DOM SSD</b>	PCIe-SSD SFF, 4 TB, Read-Intensive, hot-plug, 2.5-inch, Flash drive, 0.6 DWPD (Drive Writes Per Day for 5 years)
	PCIe-SSD SFF, 2 TB, Read-Intensive, hot-plug, 2.5-inch, Flash drive, 0.6 DWPD (Drive Writes Per Day for 5 years)
	PCIe-SSD SFF, 1 TB, Read-Intensive, hot-plug, 2.5-inch, Flash drive, 1 DWPD (Drive Writes Per Day for 5 years)
	Dual microSD 64GB Enterprise
<b>SCSI / SAS Controller</b>	Fujitsu PSAS CP400i SAS Ctrl. 12 Gbit/s 8 ports int. PCIe 3.0 x8

<b>RAID Controller</b>	<p>Fujitsu PRAID EP580i LP, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, NVMe-PCIe 8 Gbit/s, 8 Gbit/s 16 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 8 GB, Optional FBU based on LSI SAS3516</p> <p>Fujitsu PRAID EP540i LP, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, NVMe-PCIe 8 Gbit/s, 8 Gbit/s 16 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 4 GB, Optional FBU based on LSI SAS3516</p> <p>Fujitsu PRAID EP520i LP, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, NVMe-PCIe 8 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 2 GB, Optional FBU based on LSI SAS3516</p> <p>Fujitsu PRAID EP420i, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 2 GB, Optional FBU based on LSI SAS3108</p> <p>Fujitsu PRAID EP420i for SafeStore, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 2 GB, Optional FBU based on LSI SAS3108</p> <p>Fujitsu PRAID EP400i, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 1 GB, Optional FBU based on LSI SAS3108</p> <p>Fujitsu PRAID CP400i, RAID Ctrl., SAS/SATA 12 Gbit/s, 8 ports int. RAID level: 0, 1, 1E, 10, 5, 50, No FBU support</p>
<b>Communication, Network</b>	<p>Converged Network Adapter 2 x 10 Gbit/s / 25 Gbit/s PCIe 3.0 x8 SFP28 ( Cavium )</p> <p>Ethernet Ctrl. 2 x 10 Gbit/s ; 1 Gbit/s PCIe 3.0 x8 RJ45 ( Cavium )</p> <p>Ethernet Ctrl. 2 x 10 Gbit/s ; 1 Gbit/s PCIe 3.0 x8 RJ45 ( Intel® )</p> <p>Ethernet Ctrl. 2 x 10 Gbit/s ; 1 Gbit/s PCIe 3.0 x8 SFP+ ( Cavium )</p> <p>Ethernet Ctrl. 2 x 10 Gbit/s / 25 Gbit/s PCIe 3.0 x8 SFP28 ( Cavium )</p> <p>Ethernet Ctrl. 2 x 10 Gbit/s / 25 Gbit/s PCIe 3.0 x8 SFP28 ( Intel® )</p> <p>Ethernet Ctrl. 2 x 10 Gbit/s / 25 Gbit/s PCIe 3.0 x8 SFP28 ( Mellanox )</p> <p>Ethernet Ctrl. 2 x 10 Gbit/s PCIe 3.0 x8 SFP+ ( Intel® )</p> <p>Ethernet Ctrl. 2 x 1 Gbit/s PCIe 2.1 x4 RJ45 ( Intel® )</p> <p>Ethernet Ctrl. 4 x 10 Gbit/s ; 1 Gbit/s PCIe 3.0 x8 RJ45 ( Intel® )</p>
<b>Graphics add on cards</b>	NVIDIA® Quadro® P400 , 2 GB, PCIe x16, 3x miniDP
<b>Warranty</b>	
<b>Warranty period</b>	1 year
<b>Warranty type</b>	Onsite Service
<b>Warranty Terms &amp; Conditions</b>	<a href="http://support.ts.fujitsu.com/warranty/Index.asp?LNG=COM">http://support.ts.fujitsu.com/warranty/Index.asp?LNG=COM</a>
<b>Product Related Services - the perfect extension</b>	
<b>Support Pack Options</b>	<p>Globally available in major business areas:</p> <p>9x5, Next Business Day Onsite Response Time</p> <p>9x5, 4h Onsite Response Time (depending on country)</p> <p>24x7, 4h Onsite Response Time (depending on country)</p>
<b>Recommended Service</b>	24x7 Onsite Service with 4h Onsite Response Time
<b>Service Lifecycle</b>	5 years after end of product life
<b>Service Weblink</b>	<a href="http://www.fujitsu.com/fts/products/product-support-services/">http://www.fujitsu.com/fts/products/product-support-services/</a>



# More information

## Fujitsu products, solutions & services

In addition to Fujitsu PRIMERGY TX1320 M4, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

### Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

### Computing Products

[www.fujitsu.com/global/products/computing/](http://www.fujitsu.com/global/products/computing/)

### Software

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

## More information

To Learn more about Fujitsu PRIMERGY TX1320 M4, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

<http://www.fujitsu.com/fts/products/computing/servers/primergy/tower/>

## Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



## Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>

Copyright 2019 FUJITSU LIMITED

## Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

**Contact**  
FUJITSU LIMITED

Website: [www.fujitsu.com](http://www.fujitsu.com)  
2019-01-18 WW-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>  
Copyright 2019 FUJITSU LIMITED