

---

# Epson TM-L90LF (665): Serial, built-in USB, PS, EDG, Liner-free

---

DATASHEET / BROCHURE



This thermal POS printer produces quality labels and receipts with ease.

A thermal receipt printer from Europe's number one POS printer manufacturer<sup>1</sup>, the TM-L90 Liner-free is compatible with liner-free adhesive media. It enables businesses to print adhesive-backed receipts, providing a reliable method for labelling customers' food and drink orders to ensure they are correct.

#### Uses standard and adhesive-backed paper

As the TM-L90 Liner-free works with both standard thermal receipt paper and NCR liner-free label paper, users only need one greyscale printer model for receipts and order labels. Advanced graphic printing capabilities allow for highly customized layouts for receipts and labels. Logos and promotional messages can be added with ease.

#### Easy media switching

It is compatible with 40, 58 and 80mm paper widths.

#### Saves paper

The printer's sensor for media with black marks enables it to cut the receipt between areas of adhesive. However, it can also be set up to cut through adhesive areas, which saves paper. To further reduce paper consumption, the automatic top margin reduction function prints the top of the next receipt before cutting the current one when printing continues after auto cutting.

#### Reduces bills and environmental impact

The power-efficient TM-L90 Liner-free is qualified by ENERGY STAR when used with Epson's PS180 power supply.

#### Flexible installation

Users can position the printer in the most convenient spot, thanks to a choice of vertical, horizontal or wall-mounted (using optional bracket) installation. It comes with a built-in USB interface in addition to the serial interface.

---

## KEY FEATURES

---

- **Reliable labelling**  
Improves order accuracy
- **Media flexibility**  
Uses standard and NCR paper
- **Saves paper**  
Auto top margin reduction
- **Reduces bills**  
Power-efficient
- **Easy installation**  
Three mounting positions

## PRODUCT SPECIFICATIONS

Print method	Thermal line printing
Print speed	170 mm/sec
<b>PAPER</b>	
Paper size	79,50 ± 0,50 (W) mm x dia 102,00 mm, 58,00 ± 0,50 (W) mm x dia 102,00 mm, 40,00 ± 0,50 (W) mm x dia 102,00 mm
<b>FONTS &amp; STYLES</b>	
Print Speed (label)	90 mm/sec
Print Speed receipt	170 mm/sec
Print Speed	90 mm/sec
Printing Font	ANK
Character set	95 Alphanumeric, 37 International, 128 x 11 Graphic
Dot density	203 DPI x 203 DPI
Printing Characters	Text (incl. Euro symbol), Graphics
<b>INTERFACES</b>	
Interfaces	USB 2.0 Type B, Drawer kick-out, RS-232
<b>POWER</b>	
Power Supply	PS-180
Power Consumption	Standby: 0,1 A, Mean: 1,8 A
Operating Voltage	24 V
<b>GENERAL</b>	
Product dimensions	140 x 148 x 203 mm (Width x Depth x Height)
Product weight	1,9 kg
Colour	Epson Dark Grey
Noise Level	Operation (Roll): 52 dB (A)
<b>DATA BUFFER</b>	
Data Buffer	4 kB or 45 Bytes
<b>OTHER</b>	
Warranty	12 months Carry in Optional warranty extension available

## LOGISTICS INFORMATION

SKU	C31C412665
EAN code	8715946551920
Country of Origin	China
Layer	16 Units

Epson TM-L90LF (665): Serial,  
built-in USB, PS, EDG, Liner-free

## WHAT'S IN THE BOX

- Main unit
- User manual
- Warranty document
- PS-180
- Paper roll spacer

## OPTIONAL ACCESSORIES

- WH-10 (040) Wall hanging bracket  
C32C845040
- UB-E04: 10/100 BaseT Ethernet I/F Board  
C32C881008

Co<sup>ver</sup>Plus

Epson Europe B.V. (Holland) Filial Sverige  
Support: +46 8-5051 3701  
level.one@epson.se  
www.epson.se

Finlandsgatan 10  
164 74 Kista  
Öppettider Support: 09.00 – 17.00

Varumärken och registrerade varumärken tillhör Seiko Epson Corporation eller Epsons respektive ägare.  
Produktinformation kan ändras utan förvarning.

1. 1Source: Interconnection Consulting, 2010

**EPSON**®