



## White USB-C to HDMI Cable 3m (9.8ft)

TC 3MUSBCHDMI EU SAP: 4322274 US SAP: 12939455

[vav.link/tc\\_3musbchdmi](http://vav.link/tc_3musbchdmi)

On one end: HDMI - plugs into a display device

On the other end: USB type C - the new smaller reversible USB plug which supports USB 3.1 signal.

VISION

## CAD

---

Cad 1

**ZIP 548.54 KB**

[files.visionaudiovisual.com/products/archive/TC\\_2MUSBCHDMI/cad/TC\\_2MUSBCHDMI-1.zip](https://files.visionaudiovisual.com/products/archive/TC_2MUSBCHDMI/cad/TC_2MUSBCHDMI-1.zip)

## SPECIFICATION

---

Dims 1

**PDF 368.83 KB**

[files.visionaudiovisual.com/products/archive/TC\\_2MUSBCHDMI/specifications/TC\\_2MUSBCHDMI\\_dims-1.pdf](https://files.visionaudiovisual.com/products/archive/TC_2MUSBCHDMI/specifications/TC_2MUSBCHDMI_dims-1.pdf)

## IMAGE

---

Product Images

**ZIP 1.77 MB**

[files.visionaudiovisual.com/products/TC\\_3MUSBCHDMI/images/TC\\_3MUSBCHDMI.zip](https://files.visionaudiovisual.com/products/TC_3MUSBCHDMI/images/TC_3MUSBCHDMI.zip)

Product Images

**PNG 1.14 MB**

[files.visionaudiovisual.com/products/TC\\_3MUSBCHDMI/images/TC-2MUSBCHDMI.png](https://files.visionaudiovisual.com/products/TC_3MUSBCHDMI/images/TC-2MUSBCHDMI.png)

## SPECIFICATIONS

---

### MAXIMUM RESOLUTION

3840 x 2160 (4K) @ 60 Hz

### SHEATH: PVC, OUTER DIAMETER

4.7 mm (0.19")

### CONDUCTOR THICKNESS

32 AWG

### BANDWIDTH

480Mbit/s

### COMPLIANCE

CE, FCC

### PACKAGED WEIGHT

0.13 kg (0.29 lb)

### PRODUCT WEIGHT

0.118 kg (0.26 lb)

### PACKAGED DIMENSIONS

270 mm x 220 mm (10.6" x 8.7")

### USB 3.1 CABLE

### GOLD PLATED CONNECTORS

SUPPORTS ALT MODE WHERE CABLE USED FOR DISPLAYPORT OR HDMI SIGNAL INSTEAD OF USB

WORKS WITH IPAD