

DUAL-GTX1660TI-6G

2X Fans, 2X Fun

ASUS Exclusive Innovations

IP5X-Certified Dust Resistance

ASUS fan design is certified under the International Protection Marking (IP code) as IP5X dust resistant for improved reliability and optimal fan performance, even under severe conditions.





Auto-Extreme Technology

Fully automated manufacturing for improved reliability and lower environmental impact.

144 Hours Validation Program

Extensive stability testing with chart-topping game titles and heavy workload to ensure card reliability.







ASUS Features

6 GDDR6 Memory

• Gigantic 6GB GDDR6 Memory:

On-board memory for the best gaming experience & the best resolution.

• NVIDIA[®] HIGHLIGHTS :

Graphics GPU Features

Automatically record your best gaming moments.



• VR-FRIENDLY HDMI PORTS: Let you connect a VR device and display at the same time and enjoy immersive virtual reality experiences without having to swap cables.



• NVIDIA[®] ANSEL: : Turn screenshots into art with 360, HDR, and Super-Res photos.



• GPU TWEAK II: Comprehensive GPU performance

tweaking, XSplit Gamecaster, wtfast, and Quantum Cloud's mining App which allows gamers to utilize idle GPUs to earn low-maintenance income.



● NVIDIA[®] G-SYNC[™] TECHNOLOGY:

For the smoothest and fastest gaming imaginable, eliminating screen tearing and minimizing display stutter and input lag.




*Free 1-year premium XSplit Gamecaster (USD 99.95 /yr).

Six-month wtfast premium license — a USD\$53.95 value — to let

user enjoy online gaming that's free from lag, latency and lost packets.

I/O Specifications





| | Hardware Specification |
|-------------------------|--|
| Model | DUAL-GTX1660TI-6G |
| Graphics Engine | NVIDIA [®] GeForce [®] GTX 1660TI |
| CUDA cores | 1536 |
| OpenGL | OpenGL [®] 4.5 |
| Engine Clock | OC mode : 1800 MHz (Boost Clock) |
| | 1530 MHz (Base Clock) |
| | Gaming mode : 1770 MHz (Boost Clock) |
| | 1500 MHz (Base Clock) |
| Memory Interface | 192 bit |
| Video Memory | 6GB GDDR6 |
| Memory Clock | 12002 MHz |
| Power connectors | 1*8pin |
| I/O | 2x Native HDMI 2.0b |
| | 1x Native DisplayPort 1.4 |
| | 1x Native DVI-D |
| HDCP compliant | HDCP 2.2 |
| Digital Max Resolution | 7680 x 4320 |
| Maximum Display Support | 4 |
| SLI / Crossfire Support | N/A |
| Recommended PSU | 450W |
| Accessory Bundled | N/A |
| Bus Standard | PCIE 3.0 |
| Dimension | The card size is 21.5*12.1*4.4 cm |
| | The card size is 8.5*4.8*1.7 inches |
| Software Bundled | ASUS GPU Tweak II & Driver |
| Slot | 2.3 slot |
| Note | Specifications are subject to change without notice. |
| | • PCB color and bundled software versions are change without |
| | notice. |
| | Brand and product names mentioned are trademarks of their |
| | respective company. |



