High Contrast Ratio & Full Color

47" FULL HD NARROW-BEZEL TRANSPARENT DISPLAY 47TS50MF



HIGH VISIBILITY

Full HD (47TS50MF)

High picture quality with 1,920 x 1,080 resolution



Conventional (HD)



47TS50MF (FHD)

Superior Color Gamut With Superior Color Gamut, 47TS50MF presents more clearer image.





47TS50MF

True Color (IPS)

 LG IPS technology provides true vivid color than conventional display.



Conventional



Shine-Out (47TS50MF)

Perfect fit for window display by reflecting away the sunlight for best image visibility and clearer display under direct sunlight than conventional panel.







Conventional 47TS50M

EASY CUSTOMIZATION OPEN FRAME

47TS50MF fits to any customer need and circumstance with its open frame. It can be designed according to customer request at an affordable price.

LANDSCAPE & PORTRAIT

Flexible usage with landscape or portrait display according to the display environment.





Portrait

Landscape



FULL HD TRANSPARENT DISPLAY

47TS50MF 47F"





• 1,920 x 1,080 (FHD)

FEATURES

• High Contrast Ratio: 1,200: 1 (Typ)

• Transmittance : 6.4% (Typ)

• Color Gamut : 72%



• Shine-Out (Anti Reflection Coating)

• Bezel: 39.95 / 17.5 / 17.5 / 17.5mm (T / B / L / R)

• Easy Customization (Open Frame)

Kiosks not provided by LGE


SPECIFICATIONS

47TS50MF

PANEL	Screen Size	46.96 inch (1192.87mm) diagonal
TAREE		` , , ,
	Panel Technology	IPS
	Aspect Ratio	16:9
	Native Resolution	1,920 x 1,080 (FHD)
	Transmittance	6.4% (Typ)
	Contrast Ratio	1,200 : 1 (Typ)
	Response Time	9ms (G to G, *WOT)
	Viewing Angle (H x V)	178 x 178
CONNECTIVITY	Input (Rear)	
	Digital	LVDS(1)
	Analog	N/A
	Audio	N/A
	External Control	N/A
	USB	N/A
	Output (Rear)	
	Digital	N/A
	Analog	N/A
	Audio	N/A
	External Control	N/A
PHYSICAL SPECIFICATION	Bezel Width	39.95mm(Top), 17.5mm(Bottom / Left / Right)
	Monitor Dimension (W x H x D)	1084.48mm x 653.02mm x 11.2mm
	Weight (head)	2.9kg

PHYSICAL SPECIFICATION	Carton Dimensions (W x H x D)	1190mm x 760mm x 125mm
	Packed Weight	6.3kg
	VESA TM Standard Mount Interface	N/A
SPECIAL FEATURES	Additional	Color Gamut (72%)
ENVIRONMENT CONDITIONS	Operation Temperature	0°C ~50°C
	Operation Humidity	10% ~ 90%
POWER	Power Supply	N/A
	Power Consumption	
	Typical / Smart Energy Saving (on)	6.1W (12V Input)
	DPMS	N/A
	Power Off	N/A
Standard(Certification)	Safety	N/A
	EMC	N/A
	ErP / Energy Star	N/A
MEDIA PLAYER COMPATIBILITY	Slot PC Compatible (optional)	N/A
	External Media Player Attachable	N/A
OFTWARE COMPATIBILITY	Supersign Compatibility	N/A
ACCESSORY	Included	CD Manual(1)
	Optional	N/A

DIMENSION (unit:mm)





 $^{^*}$ WOT : Within Operation Temperature $\,\,^*$ Image may differ slightly from actual product. Specifications are subject to change without prior notice.