

Data Sheet

Fujitsu 43 cm / 17-inch TFT rack console RC25

User-friendly rack console (only 1 U)

The rack consoles from Fujitsu Technology Solutions are specially designed for installation in 19-inch rack systems. The console is secured on guide rails and is a component of the central control unit in server systems.

The rack console opens just like a laptop as soon as it leaves the rack housing; the central monitor unit and input interfaces then become accessible. Several rack servers can be easily and securely managed via the rack console.

43 cm / 17-inch TFT rack console RC25

Standard racks enable reliable and maintenance-friendly operation of servers and other 19-inch rack systems. The rack console RC25 is an ergonomically optimized, central administration workplace within a rack. In a single height unit it is used to manage rack systems easily and reliably with optimized space and energy consumption. The RC25 console has various national keyboard layouts and can integrate an analog KVM switch behind the console as well as have optionally an

external USB drive directly connected to the front USB port of the console.



Main Features	Benefits
<ul style="list-style-type: none"> ■ 43cm/17-inch TFT flat screen display ■ Keyboard with 87-92 keys in various languages ■ Integrated touchpad ■ Out-of-band management ■ Rack mount kit, cable and cable management integrated 	<ul style="list-style-type: none"> ■ Brilliant display for eye friendly usage ■ Keyboard is MS Windows® compatible, Windows shortcut keys ■ Scroll function as well as additional left and right-hand mouse key ■ Reliable secure access to KVM switch or server ■ Tool less rack installation, 1 U rack space, detend slides, ergonomic work, secure cable guides
<ul style="list-style-type: none"> ■ Virtual Media Port ■ KVM integration in same U space 	<ul style="list-style-type: none"> ■ Front USB passthrough with compatible KVM switches ■ Optional mounting of analog KVM switches from Fujitsu Technology Solutions

Technical details

Technical details

Screen diagonal	43.18 cm (17-inch), 4:3
Display data (typical)	Brightness: 200 cd/m ² , Contrast: 450:1 (TYP), Viewing angle: H:80° V:80°, Up to 16.7 million colours, Reaction time 5ms (typ.)
Pixels	1280 x 1024 (SXGA) / multi-frequency feature (H= 30 -61 kHz; V = 55 – 75 Hz), dot pitch =0.26 mm
Note	(Note: max. resolution may be limited by input devices)
Plug & Play	VESA Sun composite
Energy efficient	Monitor pushed in, protected and automatically switched into power save mode.
MTBF / lifespan illumination	50,000 / 25,000 hours for the backlight luminosity to halve
Setting options	Brightness, contrast; horizontal and vertical picture); picture size (horizontal und vertical); colour and individual colour settings; auto-setting and phase/frequency control; language menu, position OSD languages: German, English, French, Spanish, Italian or Japanese
Connections / cables / documentation	Connection for PS2 or USB and VGA; 3m cable included in delivery scope: combi VGA/PS/2, USB and power connection manual on CD-ROM, Safety notes, Quick start guide
Keyboard Type	87-92 keys, country specific keyboard layouts, Microsoft® compatible; Solaris compatible (function keys), Inverted T scroll keys, 2 button touch pad with scrolling, Available country versions: D/US, US, UK, F, ESP, I, DK, B , SE, PT, US/RUS (cyrilic) JPN, TR (April 2011)

Environmental

Operating ambient temperature	Recommended range 10° - 35°C, tolerance limits -20° - 60°C
Operating relative humidity	20 - 80 % (relative humidity); 10 - 85% (no condensation)

Electrical values

Nominal voltage / mains connection	100 V - 240 V, 50-60 Hz; IEC320-C14 (international) NEMA5-15 (Japan)
Power consumption	max. 30 W / max. 3 W standby
Protection class	IP20

Dimensions / Weight

Dimensions (W x D x H)	486 x 444 x 42.5 mm (depth without rack mount kit and closed monitor)
Transport Dimensions (W x D x H)	540 x 940 x 170 mm (delivery package)
Weight	14 kg (with rack mounting kit)

Approvals & Conformity (Standards)

Germany	GS
Europe	CE EN
USA/Canada	FCC Class A UL/cUL
Global	CB WEEE (Waste electrical and electronical equipment) RoHS (Restriction of hazardous substances)
Japan	VCCI Class A
China	CCC
Australia/New Zealand	C-Tick
Taiwan	BSMI
Argentina	IRAM
Mexico	NOM
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/default.aspx

More information

Fujitsu platform solutions

In addition to Fujitsu 43 cm / 17-inch TFT rack console RC25, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu 43 cm / 17-inch TFT rack console RC25, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
<http://ts.fujitsu.com/Primergy>

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT. Please find further information at <http://www.fujitsu.com/global/about/environment/>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

Contact

FUJITSU LIMITED
Mies-van-der-Rohe-Straße 8
80807 München
Germany
Website: www.ts.fujitsu.com
2011-02-18 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions