**10C** 

# No stuttering, no tearing, just gaming.





AOC G2778VQ 27"
AMD FreeSync™ Gaming Monitor









Narrow Bezel Design FreeSync Gaming Monitor Flicker Free Tech for Eye Care Clear Vision Off Timer, e-Saver, i- Menu, Screen+



## **Features**



AMD FreeSync technology synchronizes the GPU and the monitor so frames are displayed when ready: no tearing or stuttering

- Why FreeSync is better
   High performance solution with all the benefits of variable refresh rate technology
- Based on industry standards, not expensive proprietary solutions
- Cheaper and easier to implement: no additional monitor hardware, no license fees



Most LED monitors use PWM (pulse width modulation) to control brightness; the pulsing creates flicker that may cause discomfort, headaches and eye strain, especially in low-light environments. Flicker Free technology uses a smooth DC (direct current) backlight





### ms Fast Response Time

Fast 1ms (GTG) screen response displays moving images without



HDMI 1.4 is a popular digital video and sound connection standard. DisplayPort 1.2 is capable of higher performance and convenience than older digital formats.



With AOC Shadow Control, gamers can dial-in shadow levels in the OSD Menu to increase contrast for better dark area definition without affecting the rest of the screen.





- If picture is too dark to see the details clearly, adjusting up from 50 to 100 will lighten the dark portions.
- If picture is too bright and washed out. Adjusting down from 50 to 0 provides dark definition.

## Specifications

Model Name	G2778VQ
Panel size	27"
Screen Ratio	16:9
Response Time (Typical)	1ms
Recommended Resolution	1920x1080
Contrast Ratio	1000:1 (Typical) 80,000,000:1 (DCR)
Brightness (Typical)	300 cd/m <sup>2</sup>
Display Color	16.7M
Viewing Angle (H/V)	170/160
Viewable Image Size (mm)	686
Display Area (mm)	597.8(H)×336.3 (V)
Pixel Pitch (mm)	0.311
Scan Frequency	H:30~83KHz (VGA/HDMI) /83K~83KHz (DP)
	V:50~76Hz (VGA/HDMI ) /48~76Hz (DP)
Input Signal	Analog, HDMI & DP
Input Connector	Analog, HDMI & DP
Built-in Speaker	2W*2/Audio Out*1
HDCP Compatible	YES
Input Power	100-240VAC, 50/60Hz
Power Supply	Internal
Operating Mode (W)	32W
Standby Mode (W)	<0.5W
Wall Mount	100x100mm
Cabinet Color	Black & Red
Phys. (W×H×D) mm	640.3x470.7x299.1
Package Box (W×H×D) mm	729x555x215
Weight (Net/ Gross)kg)	5.98/8.03
Plug & Play	VESA DDC2B™ & DDC2B/CI
User Control	Source/Auto/Exit, Gaming Mode/<,
	Volume/>, Menu/Enter, Power
USB Plug	N/A
OSD Languages	16 Languages
Safety Regulation	CCC, FCC, cTUVus, CE, EPA,
	ISO9241-307, RoHS, Windows 7/8

Design and Specifications are subject to change without notice.