

## **AXIS F1004 Sensor Unit**

Super small size and price for discreet surveillance

AXIS F1004 Sensor Unit is small in size and price. For use with an AXIS F Main Unit, AXIS F1004 offers a lower cost, highly discreet sensor unit for indoor surveillance applications. AXIS F1004, which comprises a fixed lens and image sensor, provides a 720p resolution and a 102° horizontal field of view. AXIS F1004 has a detachable 8-m (26 ft.) cable for connecting to a main unit. A flush ceiling/wall mount kit is included. Optional accessories include surface and recessed mounts that enable the sensor unit to be tilted, and a 15-m (49 ft.) cable for connecting AXIS F1004 to a main unit.

- > Small size and price
- > 102° horizontal field of view
- > HDTV 720p
- > Detachable cable for easy and flexible installation





## **AXIS F1004 Sensor Unit**

| Camera               |   |
|----------------------|---|
| Image sensor         | 1/4" (effective) progressive scan RGB CMOS  |
| Lens                 | Fixed iris<br>2.1 mm, F2.2<br>Horizontal angle of view: 102°<br>Vertical angle of view: 56° |
| Resolutions          | Max. 1280x720   |
| Wide dynamic range   | WDR - Dynamic Contrast  |
| Minimum illumination | Color: 0.4 lux  |
| Shutter time         | 1/24500 s to 1/6 s  |
| Frame rate           | Max. 25/30 fps (50/60 Hz)   |

| General              |   |
|----------------------|---|
| Casing               | Zinc and plastic  |
| Operating conditions | 0 °C to 50 °C (32 °F to 122 °F)<br>Humidity: 10-85% RH (non-condensing)   |
| Storage conditions   | -40 °C to 65 °C (-40 °F to 149 °F)  |
| Approvals            | IEC/EN/UL 60950-1, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-27, IEC 60068-2-278,EN 55024, EN 61000-6-1, EN 61000-6-2, EN 61000-3-2, EN 61000-3-3, EN 50581, IEC 60529 IP3x, EN 55022 Class B, FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, C-tick AS/NZS CISPR 22 Class B, KCC KN22 Class B, KN24 |
| Dimensions           | 37.5 mm (1 1/2 in)<br>ø 16 mm (5/8 in)  |
| Weight               | 96 g (0.21 lb)  |
| Required<br>hardware | AXIS F Main Unit  |
| Included accessories | Installation Guide<br>Flush mount kit for installation in wall or ceiling   |
| Optional accessories | AXIS F7315 Cable White 15 m AXIS F8214 Dome Accessory AXIS F8224 Recessed Mount AXIS F8204 Mounting band Mounting bracket for AXIS P1214/P1214-E/P1224-E  |
| Warranty             | Axis 3-year warranty, see www.axis.com/warranty   |

More information is available at www.axis.com

