

LX-350 110V

DATASHEET / BROCHURE



Economical, 9-pin, 80-column printer from the world's leading dot matrix manufacturer*.

The highly reliable Epson LX-350 has a mean time between failure of 10,000 operating hours, and is ideal for front and back office applications needing continuous paper or multi-part stationery.

A very economical printer to run, the LX-350 helps save money with its high ribbon yield of 4 million characters and its low power consumption. Using just 1.1W in sleep mode and 27W when powered on, the LX-350 is qualified by ENERGY STAR for its excellent energy efficiency.

Easy to integrate, the LX-350 has Parallel, Serial and USB interfaces as standard, and will fit neatly onto desks thanks to its compact design and cable management system.

KEY FEATURES

- **High reliability**
MTBF of 10,000 operating hours
- **Power-efficient**
1.1W on standby, 27W powered on
- **Economical**
Ribbon yield of 4m characters
- **Easy integration**
Parallel, Serial and USB interfaces
- **Compact design**
Fits neatly onto desks

PRODUCT SPECIFICATIONS

TECHNOLOGY

Number of Pins	9 pins
Number of columns	80 columns
Printing Method	Impact dot matrix

PRINT

Printing Speed	HighSpeed-Draft: 10 cpi: 347 chars/s, 12 cpi: 357 chars/s, Draft: 10 cpi: 260 chars/s, 12 cpi: 312 chars/s, NLQ: 10 cpi: 65 chars/s, 12 cpi: 78 chars/s
Carbon Copies	4 plus one original

CONNECTIVITY

Interfaces	Bidirectional parallel, Parallel, USB 2.0 Type B
------------	--

PAPER / MEDIA HANDLING

Document Feed	Single sheet rear, Continuous media rear, Paper output rear
Paper Formats	Sheet Paper (single- and multi-layer), Continuous Paper (single- and multi-layer), Labels (single- and multi-layer), Roll Paper, Envelopes

GENERAL

Power consumption	27 Watt, 1,1 Watt (standby)
Product dimensions	348 x 275 x 154 mm (Width x Depth x Height)
Product weight	4,1 kg
Supported Temperature	Operation 5° C - 35° C, Storage 5° C - 35° C
Compatible Operating Systems	Windows 2000, Windows 7, Windows 8, Windows Vista, Windows XP
Included Software	Epson Status Monitor
Mean Time Between Failures	10.000 hours
Print Head Life	400 Million Strokes/Wire
Noise	Operation: 53 dB (A)
Memory	128 kB Included
Ribbon Yield	4000000 characters Black Draft
Supported Humidity	Operation 10% - 80%, Storage 10% - 80%

OTHER FEATURES

Emulations	ESC/P, IBM PPDS
------------	-----------------

OTHER

Warranty	24 months Carry in Optional warranty extension available
----------	---

LOGISTICS INFORMATION

SKU	C11CC24001
EAN code	8715946522043
Country of Origin	Indonesia
Layer	5 Units

LX-350 110V

WHAT'S IN THE BOX

- Main unit
- Setup guide
- User manual (CD)
- Driver and utilities (CD)
- Software (CD)
- Warranty document
- Power cable
- Ribbon

SUPPLIES

- SIDM Black Ribbon Cartridge (C13S015637)
- SIDM Black Ribbon Cartridge (C13S015647)

OPTIONAL ACCESSORIES

- Epson SIDM Paper Roll Holder for LX-300+II/1170II, FX-890/A, FX-2190, LQ-690/300+II series
C12C811141