



# EloPOS™ System

Modern. Modular. Made for Retail.

All-in-One Touchscreen Computer



Integrated Touch



Retail-Hardened



3-year warranty

## Product Overview

The versatile EloPOS System combines modern aesthetics, modular flexibility and commercial-grade reliability. Purpose-built for point of sale, EloPOS offers a 15.6-inch touchscreen display, choice of Intel 8th generation processors and an integrated expansion hub to connect the peripherals you need - whether a customer facing display, payment reader, printer, cash drawer, barcode scanner or scale. From traditional POS to self-service applications, EloPOS delivers the durability needed to survive continuous public use and is backed by Elo's standard 3-year warranty.

EloPOS utilizes the reliability-tested performance and security of Intel's 8th Generation processors, integrated Trusted Platform Modules, Intel vPro and the Windows 10 operating system. For added flexibility, EloPOS offers models with no OS - all pretested with Linux SuSE, Ubuntu and Red Hat operating systems, providing businesses the best solution for their environment.

**Optional accessories include MSR, barcode scanner, fingerprint reader, EMVs and customer facing displays.**

**USB Type-C interface that provides touch, video and power connectivity**

**Optional EloCare<sup>SM</sup> Advance Exchange Warranty - If you have an issue with your POS System, just pick up the phone and call Elo to have a replacement unit sent.\***

## EloPOS System

Specifications	i2	i3	i5
Processor	Intel® Celeron® Processor J4105 (4M Cache, up to 2.5 GHz)	Intel Core™ i3-8100T Processor (6M Smart Cache, 3.10 GHz)	Intel Core i5-8500T Processor (9M Smart Cache, up to 3.50 GHz by Intel Turbo Boost Technology 2.0) Intel vPro™ Support
TPM	TPM 2.0		
Active Management Technology	N/A		Intel AMT 11.0 Support
Chipset	N/A		Intel Q370 Express
Video	Intel UHD Graphics 600	Intel UHD Graphics 630	
BIOS	AMI		
Memory (RAM)	4GB 2400MHz DDR4 SO-DIMM on 1 of 2 slots (expandable to 8GB)	4GB 2400MHz DDR4 SO-DIMM on 1 of 2 slots (expandable to 32GB)	8GB 2400MHz DDR4 SO-DIMM on 1 of 2 slots (expandable to 32GB)
Storage	128GB 2.5" SATA SSD, 72 TBW		
Operating System Options	No OS; Microsoft Windows 10 IoT Enterprise LTSB 64-bit		
Languages	Windows 10 - 36 Language groups		
USB Ports	3 x USB 3.0 (1 on display head, 2 on I/O); 2 x USB 2.0 (on I/O); 4 x Micro USB 2.0 (on display head)		
Powered USB	1 x 24V on I/O; 2 x 12V on I/O		
Serial Ports	2 x RJ45		
Cash Drawer Port	12V/24V Cash Drawer Port on I/O (EPSON Pinout, 24V default; selectable by internal switch)		
Ethernet Port	1 x LAN RJ45 (Gigabit)		
Wireless Connectivity	802.11 a/b/g/n/ac 2.4GHz and 5GHz; Bluetooth 5.0		
Additional Video Out	1 x Full-function USB-C (Power up to 27W, USB 3.0, Display Port)		
Audio	2 x 2W internal speakers; 1 x 3.5 mm headset jack		
Display	15.6" diagonal, active matrix TFT LED LCD		
Aspect Ratio	16:9 (standard)		
Active Display Area (W x H)	13.55" x 7.62" / 344.2mm x 193.5mm		
Native (optimal) Resolution	1366 x 768 @ 60Hz		
Number of Colors	262,144		
Brightness (typical)	LCD panel: 220 nits; TouchPro PCAP: 187 nits		
Response Time Total (typical)	10 msec		
Viewing Angle (typical)	Horizontal: 45°/45° or 90° total / Vertical: 15°/35° or 50° total		
Contrast Ratio (typical)	400:1		
Touch Technologies	TouchPro® PCAP with up to 10 touches		
Power	External 24VDC universal-type power supply brick; AC input voltage: 100-240 VAC; Input frequency: 50-60 Hz; Maximum output power: 180W		
Max Power Consumption	i2 Model: 24W; i3 Model: 65W; i5 Model: 74W		
Dimensions	With Stand: 15.2" x 14.54" x 8.71" / 386.2mm x 369.3mm x 221.2mm; Without Stand: 15.2" x 9.8" x 2.89" / 386.2mm x 248.9mm x 73.3mm		
Shipping Dimensions	With Stand: 18.19" x 11.77" x 18.5" / 462mm x 299mm x 470mm; Without Stand: 18.19" x 8.5" x 13.57" / 462mm x 216mm x 346mm		
Weight	With Stand: 10.8lbs / 4.9kg; Without Stand: 6.4lbs / 2.9kg		
Shipping Weight	With Stand: 16.1lbs / 7.3kg; Without Stand: 10.8lbs / 4.9kg		
Temperature	Operating: 0°C to 35°C (32°F to 95°F); Storage: -20°C to 60°C (-4°F to 140°F)		
Humidity (non-condensing)	Operating: 20% to 80%; Storage: 5% to 95% (38.7°C max wet bulb temperature)		
Regulatory approvals and declarations	UL/cUL, FCC, TUV, CE, CB, Mexico NOM, C-Tick/RCM, VCCI, Argentina S-Mark, CCC		
Mounting Options	75mm VESA mount		
Warranty	3-year warranty extendable up to 5 years		
Extended Warranty Options	1 year extended warranty - Elo P/N: E819394; 2 year extended warranty - Elo P/N: E819598 3 year EloCare Advance Exchange - Elo P/N: 819795; 4 year EloCare Advance Exchange + 1 year extended warranty - Elo P/N: 819985; 5 year EloCare Advance Exchange + 2 year extended warranty - Elo P/N: 820186		
MTBF	50,000 hours demonstrated		
What's in the box	EloPOS, NA Power Cord, EU Power Cord, Power Adapter - 180W, Cable RJ-45 to DB-9, Cable cover locking screw, QIG		

## Ordering Information

Part Number	Part Description	Processor	OS	Memory	Surface Treatment	Touch Interface
E440439	EPS15E2-2UWA-1-MT-4G-1S-NO-00-BK	J4105	None	4GB	Antiglare	USB
E440234	EPS15E2-2UWA-1-MT-4G-1S-W1-64-BK	J4105	Window 10	4GB	Antiglare	USB
E441010	EPS15E2-2UWA-1-MT-4G-1S-NO-00-BK-NS-EXP	J4105	None	4GB	Antiglare	USB
E440808	EPS15E2-2UWA-1-MT-4G-1S-W1-64-BK-NS-EXP	J4105	Window 10	4GB	Antiglare	USB
E441385	EPS15E3-2UWA-1-MT-4G-1S-NO-00-BK	i3-8100T	None	4GB	Antiglare	USB
E441193	EPS15E3-2UWA-1-MT-4G-1S-W1-64-BK	i3-8100T	Window 10	4GB	Antiglare	USB
E441781	EPS15E3-2UWA-1-MT-4G-1S-NO-00-BK-NS-EXP	i3-8100T	None	4GB	Antiglare	USB
E441575	EPS15E3-2UWA-1-MT-4G-1S-W1-64-BK-NS-EXP	i3-8100T	Window 10	4GB	Antiglare	USB
E442161	EPS15E5-2UWA-1-MT-8G-1S-NO-00-BK	i5-8500T	None	8GB	Antiglare	USB
E441968	EPS15E5-2UWA-1-MT-8G-1S-W1-64-BK	i5-8500T	Window 10	8GB	Antiglare	USB
E442550	EPS15E5-2UWA-1-MT-8G-1S-NO-00-BK-NS-EXP	i5-8500T	None	8GB	Antiglare	USB
E442365	EPS15E5-2UWA-1-MT-8G-1S-W1-64-BK-NS-EXP	i5-8500T	Window 10	8GB	Antiglare	USB

To find out more about our extensive range of Elo touch solutions, go to [elotouch.com](http://elotouch.com), or call the office nearest you.

### North America

Tel +1 408 597 8000  
Fax +1 408 597 8050  
elosales.na@elotouch.com

### Europe

Tel +32 (0)16 70 45 00  
Fax +32 (0)16 70 45 49  
EMEA.Sales@elotouch.com

### Asia-Pacific

Tel +86 (21) 3329 1385  
Fax +86 (21) 3329 1400  
www.elotouch.com.cn

### Latin America

Tel +52 55 2281-6958  
elosales.latam@elotouch.com

\* Available for customers within the United States and Canada. Conditions apply.

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo, EloCare, EloPOS and TouchPro are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners. © 2019 Elo Touch Solutions, Inc. All rights reserved. 19014AES00116

