

FWD-65A9G

65" BRAVIA MASTER Series 4K Ultra HD, HDR, OLED Professional Display



Overview

Make an impressive statement with exquisite 4K HDR images, effortless style and sound to match

Add unprecedented impact to your visual communications with the stunningly styled, fully featured FWD-65A9G 65" BRAVIA MASTER Series OLED Professional Display. Combining bright, beautiful 4K HDR image quality with easy operation, flexible networking/control and extensive integration options, it's an imposing addition to corporate boardrooms, lobbies and reception areas.

Optimised for professional display applications, the BRAVIA MASTER Series takes full advantage of cutting edge OLED display technologies, harnessing our $X1^{\text{TM}}$ Ultimate picture processor to ensure vibrant high-contrast 4K HDR images.

The sleek, minimalist design of the FWD-65A9G is sure to impress in any setting. And with Acoustic Surface Audio $+^{\text{TM}}$, powerful cinematic sound comes directly from the 65" screen without the need for surrounding speakers.

It's easy to create attractive digital signage, mixing media files and online content with no need for additional player hardware. There's also a wide range of APIs (Application Programming Interface) options to enable remote control/monitoring and integration with external systems.

Android TV makes your professional display experience even smarter, allowing you to search apps and content with easy hands-free voice searches.

Integration in corporate environments is simplified by Pro mode that allows easy customisation of display settings to suit different applications.

Features

4K image resolution (3840 x 2160 pixels)

4K offers four times the detail of Full HD, with a resolution of over 8 million pixels bringing extra clarity to corporate display, education and digital signage application

High contrast OLED screen technology

Each self-illuminating pixel is precisely and individually controlled, with Pixel Contrast Booster technology maximising dynamic range for exquisite images with unprecedented colour contrast. You'll see unprecedented detail, texture and realism in every scene.

Spectacularly lifelike 4K images

Our most powerful ever Picture Processor X1™ Ultimate features Object-based Super



Resolution, Object-based HDR remaster and Super Bit Mapping™ 4K HDR for exceptionally detailed, realistic pictures with rich colour and ultra-low noise.

More colour with TRILUMINOS Display

TRILUMINOS Display maps colours from a wider palette, faithfully reproducing a world of richer, more lifelike hues and tones.

Smoother movement

Motionflow XR inserts additional picture frames between the originals, ensuring smoother, sharper detail in fast-moving sequences.

Optimised for professional use

The FWD-65A9G meets the needs of today's business and educational environments, with flexible installation options plus wired or wireless network connection and serial communication control.

Easily create digital signage

Integrated support for HTML5 makes it easy to produce compelling digital signage, with no extra hardware or prior training needed. Combine graphics, text, 4K video and live web content to create attractive signage in minutes.

Sound from the screen

With Acoustic Surface Audio+™, sound comes directly from the screen. Three actuators behind the TV vibrate to create acoustics that move with the picture. Two side-facing subwoofers deliver rich, spatial bass.

Centre Speaker Mode

Use your BRAVIA display as a centre speaker, delivering exeptional audio clarity in conjunction with additional speaker systems.

Do more with Android TV

Discover a world of apps and online content powered by Android TV. Use Voice Search to find content easily with no typing.

Quick set-up with Pro Mode

Customise and store display settings and features, then copy them easily to multiple displays via USB flash memory.

Specifications

DVB-T / T2
1 (Digital / Analog)
OLED
Wide zoom / Normal / Full / Zoom / 14:9
Yes
4K X-Reality PRO



Motionflow	Motionflow XR, Auto mode
Compatible with HDR	Yes (HDR10, HLG, Dolby Vision)
Video Signal	4096 x 2160p (24, 50, 60Hz), 3840 x 2160p (24, 25, 30, 50, 60Hz), 1080p (30, 50, 60, 100, 120Hz), 1080 / 24p, 1080i (50, 60Hz), 720p (30, 50, 60Hz), 720 / 24p, 576p, 480p
Audio specs	
Speaker position	Front
Audio Power Output	20W + 20W + 10W + 10W
Network specs	
Wi-Fi direct	Yes
Wi-Fi Certified	Yes
DLNA	Home Network Client, Home Network Renderer
Miracast (screen mirorring)	Yes (only for B2B purpose)
Firmware update	Yes
Internet Browser	Vewd
Wireless LAN	Integrated
Convenience features	
USB Play (contents)	MPEG1:MPEG1 / MPEG2PS:MPEG2 / MPEG2TS (HDV, AVCHD):MPEG2, AVC / MP4 (XAVC S):AVC, MPEG4, HEVC / AVI:Xvid, MotinJpeg / ASF (WMV):VC1 / MOV:AVC, MPEG4, MotionJpeg / MKV:Xvid, AVC, MPEG4, VP8. HEVC / WEBM:VP8 / 3GPP:MPEG4, AVC / MP3 / ASF (WMA) / WAV / MP4AAC / FLAC / JPEG
On screen clock	Yes
Sleep timer	Yes
On/Off timer	Yes
Google Cast	Yes
Inputs and outputs	
HDCP	HDCP2.3 (for HDMI 1 / 2 / 3 / 4)
RF Connection Input(s)	1 (Bottom)



Digital Audio Output(s) 1 (Bottom) USB 2 (Side) / 1 (Bottom) Ethernet Connection(s) 1 (Bottom) Design features Finish (Surface Color) Black Table Top Stand Separate (assembly required) VESA® Hole Spacing Compatible Yes Eco and energy saving Screen size (measured diagonally) 65" (64.5") Power Consumption (Rated / Standard) 469W Power Consumption (in Standby) 0.5W Power Requirements AC 110-240V Power Saving Mode / Back Light Off Mode Upynamic Backlight Control Yes Light Sensor Yes AC Power Input 1 (REAR) Measurements Package Carton (WxHxD) (Approx.) Approx. 1577 x 959 x 182 mm Weight Package Carton 34 Display specifications Viewing angle (Right / Left) 178 (89 / 89) degree Viewing angle (Up / Down) 178 (89 / 89) degree Display resolution QFHD Aspect ratio 16:9	HDMI™ Connection(s) (Total)	4 (1 Side, 3 Bottom)
Ethernet Connection(s) 1 (Bottom) Design features Finish (Surface Color) Black Table Top Stand Separate (assembly required) VESA® Hole Spacing Compatible Yes Eco and energy saving Screen size (measured diagonally) 65" (64.5") Power Consumption (Rated / Standard) 0.5W Power Consumption (in Standby) AC 110-240V Power Requirements AC 110-240V Power Saving Mode / Back Light Off Mode Yes Dynamic Backlight Control Yes Light Sensor Yes AC Power Input 1 (REAR) Measurements Package Carton (WxHxD) (Approx.) Approx. 1577 x 959 x 182 mm Weight Package Carton 34 Display specifications Viewing angle (Right / Left) 178 (89 / 89) degree Display resolution QFHD	Digital Audio Output(s)	1 (Bottom)
Design features Finish (Surface Color) Black Table Top Stand Separate (assembly required) VESA® Hole Spacing Compatible Yes Eco and energy saving Screen size (measured diagonally) Power Consumption (Rated / Standard) Power Consumption (in Standby) Power Requirements AC 110-240V Power Saving Mode / Back Light Off Mode Dynamic Backlight Control Yes Light Sensor Yes AC Power Input 1 (REAR) Measurements Package Carton (WXHXD) (Approx.) Approx. 1577 x 959 x 182 mm Weight Package Carton 34 Display specifications Viewing angle (Right / Left) 178 (89 / 89) degree Viewing angle (Up / Down) 178 (89 / 89) degree Display resolution OFHD	USB	2 (Side) / 1 (Bottom)
Finish (Surface Color) Table Top Stand Separate (assembly required) VESA® Hole Spacing Compatible For and energy saving Screen size (measured diagonally) Power Consumption (Rated / Standard) Power Consumption (in Standby) Power Requirements AC 110-240V Power Saving Mode / Back Light Off Mode Dynamic Backlight Control Light Sensor Yes AC Power Input 1 (REAR) Measurements Package Carton (WxHxD) (Approx.) Approx. 1577 x 959 x 182 mm Weight Package Carton 34 Display specifications Viewing angle (Right / Left) Viewing angle (Right / Left) Display resolution QFHD	Ethernet Connection(s)	1 (Bottom)
Finish (Surface Color) Table Top Stand Separate (assembly required) VESA® Hole Spacing Compatible For and energy saving Screen size (measured diagonally) Power Consumption (Rated / Standard) Power Consumption (in Standby) Power Requirements AC 110-240V Power Saving Mode / Back Light Off Mode Dynamic Backlight Control Light Sensor Yes AC Power Input 1 (REAR) Measurements Package Carton (WxHxD) (Approx.) Approx. 1577 x 959 x 182 mm Weight Package Carton 34 Display specifications Viewing angle (Right / Left) Viewing angle (Right / Left) Display resolution QFHD		
Table Top Stand VESA® Hole Spacing Compatible Feco and energy saving Screen size (measured diagonally) Power Consumption (Rated / Standard) Power Consumption (in Standby) Power Requirements AC 110-240V Power Saving Mode / Back Light Off Mode Dynamic Backlight Control Light Sensor AC Power Input Measurements Package Carton (WxHxD) (Approx.) Approx. 1577 x 959 x 182 mm Weight Package Carton 34 Display specifications Viewing angle (Right / Left) Display resolution QFHD	Design features	
VESA® Hole Spacing Compatible Eco and energy saving Screen size (measured diagonally) Power Consumption (Rated / Standard) Power Consumption (in Standby) Power Requirements AC 110-240V Power Saving Mode / Back Light Off Mode Dynamic Backlight Control Light Sensor AC Power Input 1 (REAR) Measurements Package Carton (WxHxD) (Approx.) Approx. 1577 x 959 x 182 mm Weight Package Carton 34 Display specifications Viewing angle (Right / Left) Display resolution QFHD	Finish (Surface Color)	Black
Eco and energy saving Screen size (measured diagonally) Power Consumption (Rated / Standard) Power Consumption (in Standby) Power Requirements AC 110-240V Power Saving Mode / Back Light Off Mode Dynamic Backlight Control Light Sensor AC Power Input 1 (REAR) Measurements Package Carton (WxHxD) (Approx.) Weight Package Carton 34 Display specifications Viewing angle (Right / Left) Display resolution O.5W Yes AC 110-240V Yes LIGHT Sensor Yes AC Power Input 1 (REAR) Approx. 1577 x 959 x 182 mm Display specifications Viewing angle (Right / Left) 178 (89 / 89) degree Display resolution QFHD	Table Top Stand	Separate (assembly required)
Screen size (measured diagonally) Power Consumption (Rated / Standard) Power Consumption (in Standby) Power Requirements AC 110-240V Power Saving Mode / Back Light Off Mode Dynamic Backlight Control Light Sensor Yes AC Power Input 1 (REAR) Measurements Package Carton (WxHxD) (Approx.) Approx. 1577 x 959 x 182 mm Weight Package Carton 34 Display specifications Viewing angle (Right / Left) Viewing angle (Up / Down) Display resolution QFHD		Yes
diagonally) Power Consumption (Rated / Standard) Power Consumption (in Standby) Power Requirements	Eco and energy saving	
Standard) Power Consumption (in Standby) Power Requirements AC 110-240V Power Saving Mode / Back Light Off Mode Dynamic Backlight Control Yes Light Sensor Yes AC Power Input 1 (REAR) Measurements Package Carton (WxHxD) (Approx.) Approx. 1577 x 959 x 182 mm Weight Package Carton 34 Display specifications Viewing angle (Right / Left) 178 (89 / 89) degree Viewing angle (Up / Down) 178 (89 / 89) degree Display resolution QFHD		65" (64.5")
Standby) Power Requirements AC 110-240V Power Saving Mode / Back Light Off Mode Dynamic Backlight Control Light Sensor AC Power Input 1 (REAR) Measurements Package Carton (WxHxD) (Approx.) Approx. 1577 x 959 x 182 mm Weight Package Carton 34 Display specifications Viewing angle (Right / Left) Display resolution OFHD		469W
Power Saving Mode / Back Light Off Mode Dynamic Backlight Control Yes Light Sensor AC Power Input 1 (REAR) Measurements Package Carton (WxHxD) (Approx.) Approx. 1577 x 959 x 182 mm Weight Package Carton 34 Display specifications Viewing angle (Right / Left) Display resolution Very Market Saving Mode / Back Yes Yes 1 (REAR)	-	0.5W
Light Off Mode Dynamic Backlight Control Yes Light Sensor AC Power Input 1 (REAR) Measurements Package Carton (WxHxD) (Approx.) Approx. 1577 x 959 x 182 mm Weight Package Carton 34 Display specifications Viewing angle (Right / Left) Display resolution QFHD	Power Requirements	AC 110-240V
Light Sensor AC Power Input 1 (REAR) Measurements Package Carton (WxHxD) (Approx.) Approx. 1577 x 959 x 182 mm Weight Package Carton 34 Display specifications Viewing angle (Right / Left) Display resolution Package Carton 178 (89 / 89) degree Viewing angle (Up / Down) Display resolution QFHD	_	Yes
AC Power Input 1 (REAR) Measurements Package Carton (WxHxD) (Approx.) Approx. 1577 x 959 x 182 mm Weight Package Carton 34 Display specifications Viewing angle (Right / Left) 178 (89 / 89) degree Viewing angle (Up / Down) 178 (89 / 89) degree Display resolution QFHD	Dynamic Backlight Control	Yes
Measurements Package Carton (WxHxD) (Approx. 1577 x 959 x 182 mm Weight Package Carton 34 Display specifications Viewing angle (Right / Left) 178 (89 / 89) degree Viewing angle (Up / Down) 178 (89 / 89) degree Display resolution QFHD	Light Sensor	Yes
Package Carton (WxHxD) (Approx.) Approx. 1577 x 959 x 182 mm Weight Package Carton 34 Display specifications Viewing angle (Right / Left) Viewing angle (Up / Down) 178 (89 / 89) degree Viewing angle (Up / Down) Display resolution QFHD	AC Power Input	1 (REAR)
Package Carton (WxHxD) (Approx.) Approx. 1577 x 959 x 182 mm Weight Package Carton 34 Display specifications Viewing angle (Right / Left) Viewing angle (Up / Down) 178 (89 / 89) degree Viewing angle (Up / Down) Display resolution QFHD		
Weight Package Carton Display specifications Viewing angle (Right / Left) Viewing angle (Up / Down) Display resolution QFHD	Measurements	
Package Carton Display specifications Viewing angle (Right / Left) Viewing angle (Up / Down) 178 (89 / 89) degree Display resolution QFHD	_	Approx. 1577 x 959 x 182 mm
Display specifications Viewing angle (Right / Left) 178 (89 / 89) degree Viewing angle (Up / Down) 178 (89 / 89) degree Display resolution QFHD	Weight	
Viewing angle (Right / Left)178 (89 / 89) degreeViewing angle (Up / Down)178 (89 / 89) degreeDisplay resolutionQFHD	Package Carton	34
Viewing angle (Up / Down) 178 (89 / 89) degree Display resolution QFHD	Display specifications	
Display resolution QFHD	Viewing angle (Right / Left)	178 (89 / 89) degree
	Viewing angle (Up / Down)	178 (89 / 89) degree
Aspect ratio 16:9	Display resolution	QFHD
	Aspect ratio	16:9



OS	Android 8.0 Oreo
Signage specs	
Easy HTML5 Signage embedded	Yes
Multicast / IPTV	Yes
Control specs	
Hotel Mode Pro	Yes
IP Control	Yes
HDMI auto wake-up	Yes

Gallery





