

IZ2/UD2 Series







PROFILE

A small, affordable, energy-efficient hardware platform that can be VESA mounted on the back of a monitor (optional). The DVI-I port supports dual monitors with an optional Y-Cable and it can connect to common peripherals with its four USB ports.

FEATURES AND BENEFITS

▶ Slim Design

The perfect companion for any workplace due to the small form factor and the latest design.

► Excellent price performance

Very affordable price as Zero Client as well as Universal Desktop Thin Client.

Dualview support

The DVI-I port offers the possibility to connect one digital and one analog monitor via the optional Y-Cable.

► VESA mountable (optional)

Mountable on the back of a monitor with the optional available VESA bracket, ideal for space constrained environments.

No moving parts, e.g. cooling fans

The absence of moving parts means the devices are almost noiseless and fail-safe with minimal heat generation.

Free evaluation:

www.igel.com/evaluation



DEVICES

Zero Clients

IZ2 HDX IZ2 RFX

IZ2 Horizon

Universal Desktop

UD2 LX

Free evaluation:

www.igel.com/evaluation

COLOR



black

PERIPHERAL INTERFACES



thin clients development

services



Microsoft Partner





IGEL IZ2/UD2 SPECIFICATIONS

SYSTEM	
Available Operating Systems	IGEL Linux v5 (LX)
Management	IGEL Universal Management Suite included
Form Factor	Standard Desktop
Processor	VIA Eden ULV 1 GHz
Chipset	VIA VX855
MEMORY	
RAM	1 GB
Flash Memory	2 GB
GRAPHICS	
Chipset	VIA Chrome9
Video Memory	64-256 MB shared memory
Ports	1 x DVI-I (DVI-to-VGA adapter included)
Supported Resolutions	1920 x 1200, Dualview
NETWORK	and the second s
Ethernet	10/100/1000 Base-T
AUDIO	
Chipset	AC97 compatible
Ports	Front: 1 x line-out, 1 x mic-in
Speakers	1 x internal
PERIPHERAL INTERFACES	
PS/2	1 x keyboard
Serial	Optional, via USB-to-Serial adapter
Parallel	Optional, via USB-to-Parallel adapter
USB 2.0	4x back
Kensington Lock	1 x back
DIMENSIONS	TA WOOL
Device (DxWxH), upright	203 x 55 x 208 mm
Packaging (DxWxH), horizontal	268 x 112 x 264 mm
Weight	1.2 kg
ENVIRONMENT	1.2 Ng
Cooling	Fanless convection
Operating Temperature	0° to 40° C (vertical)
operating remperature	0° to 35° C (horizontal, with rubber feet)
Operating Humidity	10% – 80%, non-condensing
POWER	
Input	Auto sensing 100~240 VAC / 50~60 Hz
Power Supply	External
Power Consumption: Idle / Sleep Mode	9W / 2W
OPTIONS	
VESA Mount	For mounting on the back of a monitor
Rubber Feet	For horizontal placement of the device
Dualview Y-Cable	For DVI-I to DVI-D + VGA. Connect two monitors
USB-to-Serial Adapter	For connecting peripherals that require a serial port
USB-to-Parallel Adapter	For connecting printers that require a parallel port
Shared WorkPlace (only UD2 LX)	It allows user-dependent configuration based on setting profiles

After purchase, just register with us online, and all your IGEL thin clients UD2, UD3, and UD5 will be upgraded from a standard 2-year to a 5-year hardware warranty, according to our end customer hardware warranty declaration, at no additional cost. The UD9, UD10, IZ1, IZ2 and IZ3 series will be upgraded to a 3-year hardware warranty. The warranty upgrade does not cover any additional hardware options. IGEL is a registered trademark of IGEL Technology GmbH. All hardware and software names are registered trademarks of the respective manufacturers. Errors and omissions excepted.

©09/2013 IGEL Technology | 85-EN-1-6 | WEEE-Reg.-Nr. DE 79295479

IGEL Technology Ltd | info@igel.com | www.igel.co.uk | www.igel.com/en

GERMANY	AUSTRALIA	AUSTRIA	BELGIUM	CHINA	FRANCE	THE NETHERLANDS	SINGAPORE	SWEDEN	SWITZERLAND	UNITED KINGDOM	UNITED STATES
Augsburg	Sydney	Vienna	Leuven	Hong Kong	Paris	Utrecht	Singapore	Sundsvall	Zurich	Reading	Cincinnati
Bremen				Beijing Shanghai							















