

CRx Desktop Thermal Printer



Prescription Label and Monograph Printers



Cost-effective printing solutions for the pharmacy.

With more scripts to fill, more tasks to complete, and less manpower available, workflow improvement and cost management have never been more important. CognitiveTPG's CRx printing solution benefits chain and independent pharmacy operations through:

- Reduced cost of ownership -- no toner or expensive label forms
- Increased reliability and easy maintenance
- Fast print performance (no warm-up time required) and high quality script printing
- Quiet operation in an unobtrusive and small footprint (1/4 the size of a laser printer)
- Easy integration -- includes laser printer emulation and compatibility with leading pharmacy systems
- Network ready -- includes Ethernet connectivity

CRx

Cost-Effective Printing Solutions for the Pharmacy

2" AND 4" MODELS

Technical Specifications

	2" Model	4" Model
PRINT		
Method	Direct Thermal or Thermal Transfer	Direct Thermal or Thermal Transfer
Width (max)	2.205" (56 mm)	4.153" (105.5 mm)
Length (max)	218" (5537 mm)	218" (5537 mm)
Speed (max)	6 ips (152 mm/sec) w/LCD display	6 ips (152 mm/sec) w/LCD display
Resolution	300 dpi (12 dpmm)	300 dpi (12 dpmm)
MEDIA		
Width	0.75 - 2.84" (10 mm - 72 mm)	2.4" - 4.63" (50 mm - 117 mm)
Roll Diameter (max)	8" (203 mm)	8" (203 mm)
Ribbon Length (max) (TT models only)	6500" (165 m)	5500" (140 m)
Indexing	Continuous, gap, black bar, black mark, notch/hole	Continuous, gap, black bar, black mark, notch/hole
BAR CODES	Add2, Add5, Codabar, Code39, Code93, Code 128A/B/C, D2of5, I2of5, S20f5, EAN8, EAN13, EAN128, MSI/I1, Plessey, Postnet, UPCA/A+/E/E1	
FONTS		
Bitmapped	7 styles with up to 10x10 magnification, variable boldness and spacing	
International	Sans serif font in 7 pt. sizes, up to 4x4 magnification, variable boldness and spacing	
Scalable Smooth Fonts	3 Ultra Font styles for smooth characters in any size and boldness	
Laser Printer Emulation	Standard: Courier, Univers, Arial, and Times New typefaces	
Rotations	0, 90, 180, 270 degrees	
Optional	Kanji, Korean, and OCR fonts available	
GRAPHICS	PCX and BMP formats	PCX and BMP formats
MEMORY	RAM - 16 MB, Flash - 8 MB	RAM - 16 MB, Flash - 8 MB
COMMUNICATIONS	USB-A/B, Serial or Parallel, Ethernet (internal)	USB-A/B, Serial or Parallel, Ethernet (internal)
ELECTRICAL	Auto-ranging 100-240VAC, 50-60 Hz, 24VDC output	Auto-ranging 100-240VAC, 50-60 Hz, 24VDC output
ENVIRONMENTAL	Operates at 41°F to 104°F (5°C to 40°C)	Operates at 41°F to 104°F (5°C to 40°C)
DIMENSIONS		
Width	5" (127 mm)	6.9" (175 mm)
Height	7.1" (181 mm)	7.1" (181 mm)
Depth	10.04" (255 mm)	10.04" (255 mm)
WEIGHT (DT/TT)	5.02 lbs. (2.28 kg) / 5.23 lbs. (2.38 kg)	5.91 lbs. (2.69 kg) / 6.10 lbs. (2.77 kg)
ACCESSORIES	Start-up guide, power supply and cord, Window's driver, programmer's guide, NiceLabel design software, 8" OD media roll adapter, USB cable. Optional communication cables available separately	
WARRANTY		
Printer	24 months from date of purchase (requires registration and excludes printhead)	
PROGRAMMING LANGUAGE	Cognitive Programming Language (CPL), EcPL, ZcPL, and laser printer emulation	

CognitiveTPG Headquarters

25 Tri-State International, Suite 200, Lincolnshire, IL 60069
Toll Free: 800-732-8950 Phone: 847-383-7900 Fax: 847-383-7949
www.CognitiveTPG.com
Copyright 2008 CognitiveTPG. All Rights Reserved.

