

HDMI to Composite Converter with Audio

Product ID: HD2VID



The HD2VID HDMI to Composite Video Converter (with Audio) converts a digital HDMI video source (with supporting audio) to work with analog Composite video televisions and displays in both NTSC and PAL systems.

The HDMI to Composite converter provides features that ensure the highest quality output image, such as noise reduction, frame rate conversion and adaptive contrast enhancement, while an easy to use On-Screen Display(OSD) allows you to monitor your display status. Support for a wide range of HDTV and PC input resolutions make this versatile HDMI converter a perfect solution for using newer devices with existing legacy displays.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility

Applications

- Great for use in presentations, tradeshows, conferences, retail, entertainment, and home video applications
- Ideal for converting newer HDMI devices to work with older composite or S-Video televisions

Features

- Converts HDMI source to NTSC or PAL
- Converts HDMI audio to analog stereo RCA Audio
- Supports input HDTV resolutions up to 720p (PC up to 1280x800)
- Output picture size Underscan / Overscan

- Adaptive contrast enhancement
- Supports output resolutions of 480i/576p

Hardware

Warranty	2 Years
Active or Passive Adapter	Active
AV Input	HDMI
AV Output	Composite Audio RCA
Audio	Yes
Industry Standards	Standard HDMI, DVI 1.0

Performance

Supported Resolutions	Input TV - 720p, 576p, 480p @ 60Hz PC - 1280x800, 1280x768, 1224x768, 800x600, 640x480 @ 60Hz Output 480i, 576p
Audio Specifications	Input - LPCM 2Ch, 48kHz Output - Stereo L/R

Connector(s)

Connector A	HDMI (19 pin)
Connector B	Composite Video (1 x RCA) Stereo Audio (2 x RCA)

Power

Power Source	AC Adapter Included
Input Voltage	100 - 240 AC
Input Current	0.3 A
Output Voltage	5 DC



Output Current	1A
Center Tip Polarity	Positive
Plug Type	M
Power Consumption (In Watts)	3

Environmental

Operating Temperature	0C to 40C (32F to 104F)
Storage Temperature	-20C to 60C (-4F to 140F)
Humidity	20~90% RH

Physical Characteristics

Color	White
Material	Plastic
Product Length	3.9 in [100 mm]
Product Width	2.5 in [64 mm]
Product Height	1.0 in [26 mm]
Weight of Product	2.9 oz [81 g]

Packaging Information

Package Length	4.8 in [12.3 cm]
Package Width	6.0 in [15.2 cm]
Package Height	2.2 in [57 mm]
Shipping (Package) Weight	11.3 oz [321 g]

What's in the Box

Included in Package	HDMI to Composite Converter
	Universal Power Adapter (NA/UK/EU/AU)
	Instruction Manual



****Product appearance and specifications are subject to change without notice.***

